

MACTRA™

MPZ5M3E / 3F

5MP Network Dome Camera | Motorized Focus & Zoom



Infinity



5MP
Camera



Hybrid
Light



80m
Night Vision



PoE
Powered



IP67 | IK10
RATED



Secure
Boot

Technical Specifications

The **MACTRA 5MP Network Dome Camera** delivers sharp 5MP video, robust durability, and seamless integration for reliable 24/7 surveillance in any environment

CAMERA

Sensor Resolution	5MP
Sensor Type	CMOS
Sensor Size	1/2.78"
Minimum Illumination	Color =0.01 lux , Monochrome= 0 lux
Day/Night	Auto, Manual Day Mode / Night Mode
Camera Adjustable Angle	Pan 0° to 355° Tilt 0° to 75° Rotate 0° to 355°

LENS

MPZ5M3E/3F

Focal Length	2.8 mm – 11 mm
Field of View	HFOV : 108.1° – 30.3° VFOV : 56.3° – 17.1° DFOV : 130.9° – 34.8°

Lens Mount	M14
Focus	MFZ
Aperture	F1.6–F3.3 Controllable
Iris Type	P-IRIS

ILLUMINATOR

LED Type*	Hybrid LEDs (IR LED + White LED)
No. of LEDs	3 Hybrid LEDs
IR Distance	Up to 80 meters
IR Wavelength	~850 nm
IR & White Light Control	Auto, Manual (ON/OFF/Adjustable)

VIDEO & AUDIO

Stream Capability	Triple Stream
Stream Profiles	
Main Stream	5MP (2592 × 1944)@1-25/30fps, 4MP/2K (2560 × 1440)@1-25/30fps, 2MP/FHD (1920 × 1080)@1-25/30fps, 1MP/HD (1280 × 720)@1-25/30fps
Sub Stream	1MP/HD (1280 × 720)@1-25/30fps, D1/480P (720 × 480)@1-25/30fps, VGA/360P (640 × 360)@1-25/30fps
Preview Stream	1MP/HD (1280 × 720)@1-25/30fps, D1/480P (720 × 480)@1-25/30fps, VGA/360P (640 × 360)@1-25/30fps
Video Standards	PAL/NTSC
Video Compression	H.265, H.264, MJPEG
Video Bitrate Type	128 kbps–16Mbps
Video Bitrate	CBR
Region of Interest (ROI)	Supported
Audio Bit Rate	64 Kbps
Audio Codec	G.711/PCM
OSD	Supported

IMAGE

Image Settings	Brightness, Contrast, Saturation, Hue, Sharpness, Lens Distortion Correction
Wide Dynamic Range	~120 dB
S/N Ratio	50 dB
Noise Reduction	2D/3D NR
Image Rotation	Mirror, Flip, Rotation (0°, 90°, 180°, 270°)

INTERFACE

Ethernet Interface	1 X RJ45 10 M/100 M Self-Adaptive Ethernet Port
Power Reset Key	Available
Built in Microphone*	Available
SD Card*	Up to 512GB

EVENT

Alarm Event	SD Card Connect/Disconnect, SD Card Full, Wrong Login, Box Tamper Detection
Recording Type	General, Event, Alarm, Configurable Recording Streams
Recording Storage	SD Card, FTP/FTPS

AI ANALYTICS

AI Enabled	Motion Detection Visual Tamper Detection Line Crossing Detection People Counting
Edge AI*	

SECURITY

Secure Boot	Supported
Security	User account and password protection, HTTPS, TLS 1.3/1.2, SSH/Telnet Disabled Using TLS 1.3/1.2
HTTPS Streaming	Supported
Network Authentication	Yes, 802.1x Network authentication
Firmware Upgrade	Supported
Antirollback Firmware	Supported
Web Login Protection	Supported
SD Card Encryption	Supported
Reader Interface*	Secure Channel Supported

NETWORKS

Supported Protocols	TCP/IP, HTTP, HTTPS, DHCP, SRTP/RTSPS, RTP/RTSP, SMTP, NTP, TLS/SSL, FTP/FTPS, ICMP, IGMP, ARP, UDP, 802.1x, SNMP
Interoperability	ONVIF Profile S/G/T
Max. Users Access	10 Users
Web Support	Edge, Chrome, Mozilla

Note: * For Selected Variants

Technical Specifications

ELECTRICAL

Power Supply	12V(DC); 802.3af (PoE)
Power Consumption	~ 13W

MECHANICAL

Body Material	Metal Casting (Die Casting Aluminium with Powder Coating), PC
Product Dimension	126 × 105 mm (Φ × H)
Product Weight	~750 gms
Product Color	Infinity White

ENVIRONMENT




Humidity	Less than 95% RH (Non-Condensing)
Operating Temperature	-20°C to 70°C
Storage Temperature	-30°C to 60°C
Ingress Protection	IP66, IP67, NEMA 4X
Impact Resistance	IK10

REGULATORY


Emissions	FCC PART 15
Certificates	STQC, BIS, CE
RoHS	Yes
REACH	Yes
Country of Origin	India
NDAA*	Compliant
Safety	UL 62368-1, EN 62368-1, IEC 62368-1

Note: * For Selected Variants


DIMENSIONS (MM)



Ceiling Mount




Wall Mount




ACCESSORY

Connector Kit



Power Cable



Certifications & Environmental Standards & Compliance



Ordering Details

5MP Network Dome Camera **Infinity Series**

Key Features



SD Card



Hybrid/IR



Mic



Edge AI



NDAAL



NEMA 4X

2.8 - 11 mm MFZ Lens

Dynamic Area Coverage




108.1° - 30.3°

Field of View

Description	Model-Part Code							Key Features
5MP NETWORK DOME CAMERA • Image Sensor: 1/2.78" CMOS • Lens: 2.8 - 11 mm MFZ Lens • Finish: Infinity White	MPZ5M3E-E32IU2RD	-	-	-	-	-	-	IR LEDs, On-device AI Enabled
	MPZ5M3E-E31IU1RD		-		-	-	-	IR LEDs, On-device AI Enabled, SD Card Supported, Built-In-Mic
	MPZ5M3E-E31HU1PA							IR LEDs + Hybrid LED, On-device Edge AI Supports, SD Card Supported, Built-In-Mic, NDAAL & NEMA 4X

2.8 - 11 mm MFZ Lens


Dynamic Area Coverage



108.1° - 30.3°

Field of View

Description	Model-Part Code							Key Features
5MP NETWORK DOME CAMERA • Image Sensor: 1/2.78" CMOS • Lens: 2.8 - 11 mm MFZ Lens • Reader Interface: Secure Channel Supported • Relay: 2 x Channel, • RS485: 1 x Channel, • GPIO: 4 x GPIO on Pigtail • Finish: Infinity White	MPZ5M3F-F32IU2RD	-	-	-	-	-	-	IR LEDs, On-device AI Enabled, Secure Channel
	MPZ5M3F-F31IU1RA		-			-	-	IR LEDs, On-device Edge AI Supports, Secure Channel, SD Card Supported, Built-In-Mic
	MPZ5M3F-F32HU2PD	-		-	-	-	-	Hybrid LED, On-device AI Enabled Secure Channel
	MPZ5M3F-F31HU1PA							Hybrid LED, On-device Edge AI Supports, Secure Channel, SD Card Supported, Built-In-Mic, NDAAL & NEMA 4X



MACTRA™

For more information :

☎ : +91 79 69268101 | ✉ : mactra@mactra.com | 🔗 : www.mactra.com | 📍 : India

© MACTRA™ by Mantra Softech. All Rights Reserved.

